




Advanced Swing & MVC

Custom Data Models and Cell Renderers

Originals of slides and source code for examples: <http://courses.coreservlets.com/Course-Materials/java.html>
Also see the Java 8 tutorial – <http://www.coreservlets.com/java-8-tutorial/>
and customized Java training courses (onsite or at public venues) – <http://courses.coreservlets.com/java-training.html>


Customized Java EE Training: <http://courses.coreservlets.com/>

Java 7, Java 8, JSF 2.2, PrimeFaces, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.
Developed and taught by well-known author and developer. At public venues or onsite at *your* location.



For live Java-related training, email hall@coreservlets.com

Marty is also available for consulting and development support



Taught by lead author of *Core Servlets & JSP*, co-author of *Core JSF* (4th Ed), & this tutorial. Available at public venues, or customized versions can be held on-site at your organization.

- Courses developed and taught by Marty Hall
 - JSF 2.2, PrimeFaces, servlets/JSP, Ajax, jQuery, Android development, Java 7 or 8 programming, custom mix of topics
 - Courses available in any state or country. Maryland/DC area companies can also choose afternoon/evening courses.
- Courses developed and taught by coreservlets.com experts (edited by Marty)
 - Spring, Hibernate/JPA, GWT, Hadoop, HTML5, RESTful Web Services

Contact hall@coreservlets.com for details



Topics in This Section

- **Building a simple static JList**
- **Adding and removing entries from a JList at runtime**
- **Making a custom data model**
 - Telling JList how to extract data from existing objects
 - Using toString to *display* a String but *return* a complex object upon selection
- **Making a custom cell renderer**
 - Telling JList what GUI component to use for each of the data cells

4

MVC Architecture

- **Custom data models**
 - Changing the way the GUI control obtains the data. Instead of copying data from an existing object into a GUI control, simply tell the GUI control how to get at the existing data.
- **Custom cell renderers**
 - Changing the way the GUI control displays data values. Instead of changing the data values, simply tell the GUI control how to build a Swing component that represents each data value.
- **Main applicable components**
 - JList
 - JTable
 - JTree

5

JList with Fixed Set of Choices

- **Build JList: pass strings to constructor**
 - The simplest way to use a JList is to supply an array of strings to the JList constructor. Cannot add or remove elements once the JList is created.

```
String options = { "Option 1", ... , "Option N"};  
JList<String> optionList = new JList<>(options);
```
- **Set visible rows**
 - Call setVisibleRowCount and drop JList into JScrollPane

```
optionList.setVisibleRowCount(4);  
JScrollPane optionPane =  
    new JScrollPane(optionList);  
someContainer.add(optionPane);
```
- **Handle events**
 - Attach ListSelectionListener and use valueChanged

6

Simple JList: Example Code

```
public class JListSimpleExample extends JFrame {  
    ...  
    public JListSimpleExample() {  
        super("Creating a Simple JList");  
        WindowUtilities.setNimbusLookAndFeel();  
        addWindowListener(new ExitListener());  
        Container content = getContentPane();  
        String[] entries = { "Entry 1", "Entry 2", "Entry 3",  
                             "Entry 4", "Entry 5", "Entry 6" };  
        sampleJList = new JList<>(entries);  
        sampleJList.setVisibleRowCount(4);  
        sampleJList.addListSelectionListener  
            (new ValueReporter());  
        JScrollPane listPane = new JScrollPane(sampleJList);  
        ...  
    }  
}
```

7

Simple JList: Example Code (Continued)

```
private class ValueReporter implements ListSelectionListener {  
  
    /** You get three events in many cases -- one for the  
     * deselection of the originally selected entry, one  
     * indicating the selection is moving, and one for the  
     * selection of the new entry. In the first two cases,  
     * getValueIsAdjusting returns true; thus, the test  
     * below since only the third case is of interest.  
     */  
  
    public void valueChanged(ListSelectionEvent event) {  
        if (!event.getValueIsAdjusting()) {  
            String value = sampleJList.getSelectedValue();  
            if (value != null) {  
                valueField.setText(value.toString());  
            }  
        }  
    }  
}
```

8

Simple JList: Example Output



9

JList with Changeable Choices

- **Build JList:**

- Create a DefaultListModel, add data, pass to constructor

```
String choices = { "Choice 1", ... , "Choice N"};
DefaultListModel<String> sampleModel =
    new DefaultListModel<>();
for(int i=0; i<choices.length; i++) {
    sampleModel.addElement(choices[i]);
}
JList<String> optionList = new JList<>(sampleModel);
```

- **Set visible rows**

- Same: Use setVisibleRowCount and a JScrollPane

- **Handle events**

- Same: attach ListSelectionListener and use valueChanged

- **Add/remove elements**

- Use the model, not the JList directly

10

Changeable JList: Example Code

```
String[] entries = { "Entry 1", "Entry 2", "Entry 3",
                    "Entry 4", "Entry 5", "Entry 6" };
sampleModel = new DefaultListModel<>();
for(int i=0; i<entries.length; i++) {
    sampleModel.addElement(entries[i]);
}
sampleJList = new JList<>(sampleModel);
sampleJList.setVisibleRowCount(4);
Font displayFont = new Font("Serif", Font.BOLD, 18);
sampleJList.setFont(displayFont);
JScrollPane listPane = new JScrollPane(sampleJList);
```

11


Changeable JList: Example Code (Continued)

```
private class ItemAdder implements ActionListener {
    /** Add an entry to the ListModel whenever the user
     * presses the button. Note that since the new entries
     * may be wider than the old ones (e.g., "Entry 10" vs.
     * "Entry 9"), you need to rerun the layout manager.
     * You need to do this <I>before</I> trying to scroll
     * to make the index visible.
     */

    public void actionPerformed(ActionEvent event) {
        int index = sampleModel.getSize();
        sampleModel.addElement("Entry " + (index+1));
        ((JComponent) getContentPane()).revalidate();
        sampleJList.setSelectedIndex(index);
        sampleJList.ensureIndexIsVisible(index);
    }
}
```

12

Changeable JList: Example Output



13

JList with Custom Data Model

- **Build JList**
 - Have existing data implement ListModel interface
 - getElementAt
 - Given an index, returns data element
 - getSize
 - Tells JList how many entries are in list
 - addListDataListener
 - Lets user add listeners that should be notified when an item is selected or deselected.
 - removeListDataListener
 - Pass model to JList constructor
- **Set visible rows & handle events: as before**
- **Add/remove items: use the model**

14

Custom Model: Example Code

```
public class JavaLocationListModel
    implements ListModel<JavaLocation> {
    private JavaLocationCollection collection;

    public JavaLocationListModel(JavaLocationCollection collection) {
        this.collection = collection;
    }

    public JavaLocation getElementAt(int index) {
        return(collection.getLocations()[index]);
    }

    public int getSize() {
        return(collection.getLocations().length);
    }

    public void addListDataListener(ListDataListener l) {}

    public void removeListDataListener(ListDataListener l) {}
}
```

15

Actual Data

```
public class JavaLocationCollection {
    private static JavaLocation[] defaultLocations =
        { new JavaLocation("Belgium",
                           "near Liege",
                           "flags/belgium.gif"),
          new JavaLocation("Brazil",
                           "near Salvador",
                           "flags/brazil.gif"),
          new JavaLocation("Colombia",
                           "near Bogota",
                           "flags/colombia.gif"),
          ... }; ...
}
```

- **JavaLocation has toString plus 3 fields**
 - Country, comment, flag file

16

JList with Custom Model: Example Code

```
JavaLocationCollection collection =
    new JavaLocationCollection();
JavaLocationListModel listModel =
    new JavaLocationListModel(collection);
JList<JavaLocation> sampleJList =
    new JList<>(listModel);
Font displayFont =
    new Font("Serif", Font.BOLD, 18);
sampleJList.setFont(displayFont);
content.add(sampleJList);
```

17

JList with Custom Model: Example Output



18

JList with Custom Cell Renderer

- **Idea**
 - Instead of predetermining how the JList will draw the list elements, Swing lets you specify what graphical component to use for the various entries. Attach a ListCellRenderer that has a getListCellRendererComponent method that determines the GUI component used for each cell.
- **getListCellRendererComponent arguments**
 - JList: the list itself
 - Object: the value of the current cell
 - int: the index of the current cell
 - boolean: is the current cell selected?
 - boolean: does the current cell have focus?

19

Custom Renderer: Example Code

```
public class JavaLocationRenderer extends
                                DefaultListCellRenderer {
private Map<Object,ImageIcon> iconTable =
    new HashMap<Object,ImageIcon>();
public Component getListCellRendererComponent
    (JList<?> list, Object value, int index,
     boolean isSelected, boolean hasFocus) {
    JLabel label = (JLabel)super.getListCellRendererComponent
        (list,value,index,isSelected,hasFocus);
    if (value instanceof JavaLocation) {
        JavaLocation location = (JavaLocation)value;
        ImageIcon icon = iconTable.get(value);
        if (icon == null) {
            icon = new ImageIcon(location.getFlagFile());
            iconTable.put(value, icon);
        }
        label.setIcon(icon);
        ...
    }
    return(label);
}
```

20

Custom Renderer: Example Output



21

Summary

- **Simple static JList**
 - Pass array of strings to JList constructor
- **Simple changeable JList**
 - Pass DefaultListModel to JList constructor.
 - Add/remove data to/from the model, not the JList.
- **Custom data model**
 - Have real data implement ListModel interface.
 - Pass real data to JList constructor.
- **Custom cell renderer**
 - Assign a ListCellRenderer
 - ListCellRenderer has a method that determines the Component to be used for each cell

22

© 2014 Marty Hall



Questions?

More info:

<http://courses.coreservlets.com/Course-Materials/java.html> – General Java programming tutorial

<http://www.coreservlets.com/java-8-tutorial/> – Java 8 tutorial

<http://courses.coreservlets.com/java-training.html> – Customized Java training courses, at public venues or onsite at your organization

<http://coreservlets.com/> – JSF 2, PrimeFaces, Java 7 or 8, Ajax, jQuery, Hadoop, RESTful Web Services, Android, HTML5, Spring, Hibernate, Servlets, JSP, GWT, and other Java EE training



23

Customized Java EE Training: <http://courses.coreservlets.com/>

Java 7, Java 8, JSF 2.2, PrimeFaces, JSP, Ajax, jQuery, Spring, Hibernate, RESTful Web Services, Hadoop, Android.

Developed and taught by well-known author and developer. At public venues or onsite at *your* location.